febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

febi 22806 automatic transmission fluid (ATF) Article number: 22806, 26681, 26680, 30018

1.2 Relevant identified uses of the substance or mixture and uses advised against

1 2 1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictogramsnoneSignal wordnoneHazard statementsnonePrecautionary statementsnone

Special labelling EUH210 Safety data sheet available on request.

Contains: reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates, 1,1'-[iminobis(ethyleneiminoethylene)]bis[3-(octadecenyl)pyrrolidine-

2,5-dione]. EUH208 May produce an allergic reaction.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Other hazards none

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 2 / 11

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
30 - 60	Distillates (petroleum), hydrotreated light paraffinic
	CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
	GHS/CLP: Asp. Tox. 1: H304
5 - < 15	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract)
	CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, EU-INDEX: 649-221-00-X
	GHS/CLP: Asp. Tox. 1: H304
0,1 - < 1	1,1'-[iminobis(ethyleneiminoethylene)]bis[3-(octadecenyl)pyrrolidine-2,5-dione]
	CAS: 64051-50-9, EINECS/ELINCS: 264-637-8
	GHS/CLP: Skin Sens. 1B: H317 - Aquatic Chronic 3: H412
0,1 - < 1	reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates
	EINECS/ELINCS: 417-450-2
	GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 3: H412 - Eye Irrit. 2: H319 - Skin Irrit. 2: H315

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Seek medical advice immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.

Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 3 / 11

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

The product is combustible.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Do not store together with oxidizing agents.

Keep container tightly closed.

Keep container in a well-ventilated place.

Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 4 / 11

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not applicable

DNEL

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

Industrial, inhalative, Long-term - local effects, 5,4 mg/m³/8h (Aerosol)

general population, inhalative, Long-term - local effects, 1,2 mg/m³/24h (Aerosol)

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

equirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

Eye protection If there is a risk of splashing:

Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,4 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3). > 0,4 mm: Neoprene, >480 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 5 / 11

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state liquid Color red violet

characteristic

not applicable

Odor **Odour threshold** No information available.

not applicable pH-value

Boiling point [°C] No information available. > 170 (DIN ISO 2592) Flash point [°C] Flammability (solid, gas) [°C] No information available. Lower explosion limit No information available. **Upper explosion limit** No information available.

Oxidising properties

Vapour pressure/gas pressure [kPa] < 0,01 (20°C)

ca. 0,85 (DIN 51757) (15 °C / 59,0 °F) Density [g/ml]

Bulk density [kg/m³] not applicable Solubility in water immiscible

Solubility other solvents No information available. Partition coefficient [n-octanol/water] No information available.

Kinematic viscosity ca. 33 mm²/s (40°C) (DIN 51562/T1)

ca. 7,5 mm²/s (100°C)

Relative vapour density No information available. No information available. **Evaporation speed** ca. -42 (DIN ISO 3016) Melting point [°C] **Auto-ignition temperature** No information available. Decomposition temperature [°C] No information available. Particle characteristics No information available.

Other information

pH-value [1%]

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong acids.

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 100°C.

Safety Data Sheet REACH(UK) (GB) febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 6 / 11

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Safety Data Sheet REACH(UK) (GB) febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 7 / 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Product

oral, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

LD50, oral, Rat, > 5000 mg/kg

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, oral, Rat, > 5000 mg/kg (OECD 420)

Acute dermal toxicity

Product

dermal, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

LD50, dermal, Rabbit, > 5000 mg/kg

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, dermal, Rabbit, > 5000 mg/kg (OECD 402)

Acute inhalational toxicity

Product

inhalative, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-

LC50, inhalative, Rat, > 5000 mg/m³ (4h)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LC50, inhalative, Rat, > 5 mg/l /4h(Aerosol) (OECD 403)

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation Toxicological data of complete product are not available.

May produce an allergic reaction.
Calculation method

Specific target organ toxicity —

single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity —

repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Reproduction toxicityBased on the available information, the classification criteria are not fulfilled.

CarcinogenicityBased on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 8 / 11

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information

12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)

LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)

NOEL, (72h), Pseudokirchneriella subcapitata, >= 100 mg/l (OECD 201)

NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

EL50, (48h), Daphnia magna, > 10000 mg/l (OECD 202)

EL50, (72h), Pseudokirchneriella subcapitata, > 100 mg/l (OECD 201)

LL50, (96h), Oncorhynchus mykiss, > 100 mg/l (OECD 203)

NOAEL, Oncorhynchus mykiss, > 1000 mg/l (14/28d)(QSAR Petrotox))

NOAEL, (21d), Daphnia magna, 10 mg/l (OECD 211)

12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

Biological degradability

The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Do not discharge product unmonitored into the environment or into the drainage.

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 9 / 11

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102 150104

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

NO DANGEROUS GOODS Inland navigation (ADN)

Marine transport in accordance with

IMDG

NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 10 / 11

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2021)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions

for people

no

- VOC (2010/75/CE) not applicable

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

febi 22806 automatic transmission fluid (ATF) Article number 22806, 26681, 26680, 30018



Ferdinand Bilstein GmbH + Co. KG

Date printed 23.03.2021, Revision 23.03.2021

Version 11. Supersedes version: 10

Page 11 / 11

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position none