SWAG Autoteile GmbH

42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 1 / 11

SEC	TION 1: Identification of the substance/mixture and of the company/undertaking
1.1	Product identifier

SWAG 30 10 1140 Engine Oil 0W-40 Article number: 30 10 1140, 30 10 1141, 30 10 1142, 30 10 1143, 30 10 1144

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

SWAG Autoteile GmbH Am Kiesberg 4-6

42117 Wuppertal / GERMANY Phone +49 (0)202 26454-0 Fax +49 (0)202 26454-5000 Homepage www.swag.de

 Address enquiries to

 Technical information

 Safety Data Sheet

1.4 Emergency telephone number Advisory body

+49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Eye Irrit. 2: H319 Causes serious eye irritation. Skin Sens. 1: H317 May cause an allergic skin reaction.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms	
Signal word	WARNING
Contains:	C14-16-18 Alkyl phenol
Hazard statements	H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.
Precautionary statements	 P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P261 Avoid breathing mist/vapours/spray. P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice / attention. P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P501 Dispose of contents/container in accordance with local/national regulation.

2.3 Other hazards

Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	none

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 2 / 11

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

	Range [%] Substan		
	60 - < 100 Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)		
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX		
GHS/CLP: Asp. Tox. 1: H304			
	1 - < 3 Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)		
CAS: 93819-94-4, EINECS/ELINCS: 298-577-9, Reg-No.: 01-2119543726-33-XXXX			
	GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411		
1 - < 5 Bis(nonylphenyl)amine			
CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX		3878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX	
	GHS/CL	P: Aquatic Chronic 4: H413	
	1 - < 5 C14-16-	18 Alkyl phenol	
	EINECS	S/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX	
	GHS/CL	.P: Skin Sens. 1B: H317 - STOT RE 2: H373	
	Comment on component p	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements: see SECTION 16.	
SEC	TION 4: First aid measure	es	
4.1	Description of first aid n	neasures	
	General information	Change soaked clothing.	
	Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.	
	Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.	
	Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
	Ingestion	Consult a doctor immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.	
4.2	Most important symptor	ms and effects, both acute and delayed	
		No information available.	
4.3	Indication of any immed	diate medical attention and special treatment needed	
	-	Treat symptomatically.	
		Forward this sheet to the doctor.	
SEC	TION 5. Eiro fighting mos	asures	
	TION 5. FILE-INGULING INEd		
5.1	TION 5: Fire-fighting mea		
	Extinguishing media		
	Extinguishing media	dia foam, dry powder, water spray jet, carbon dioxide	
5.2	Extinguishing media Suitable extinguishing med Extinguishing media that n be used	dia foam, dry powder, water spray jet, carbon dioxide	
5.2	Extinguishing media Suitable extinguishing med Extinguishing media that n be used	dia foam, dry powder, water spray jet, carbon dioxide nust not Full water jet	
5.2	Extinguishing media Suitable extinguishing med Extinguishing media that n be used	dia foam, dry powder, water spray jet, carbon dioxide must not Full water jet from the substance or mixture	

SWAG Autoteile GmbH

42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 3 / 11

5.3	Advice for firefighters	
		Do not inhale explosion and/or combustion gases. Use self-contained breathing apparatus.
		Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
SEC	TION 6: Accidental release measur	es
6.1	Personal precautions, protective of	equipment and emergency procedures High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.
6.2	Environmental precautions	
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.
6.3	Methods and material for contain	ment and cleaning up
		Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.
6.4	Reference to other sections	See SECTION 8+13
SEC	TION 7: Handling and storage	
7.1	Precautions for safe handling	
		Avoid formation of aerosols.
		Do not smoke. Fire class (DIN EN 2): B
		Do not eat, drink or smoke when using this product. Use barrier skin cream. Wash hands before breaks and after work. Cloths contaminated with product should not be kept in trouser pockets. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse.
7.2 Conditions for safe storage, including any incompatibilities		ding any incompatibilities
		Keep only in original container. Prevent penetration into the ground.
		Do not store together with oxidizing agents.
		Keep container tightly closed. Keep container in a well-ventilated place.
7.3	Specific end use(s)	

See product use, SECTION 1.2

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 4 / 11

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³

DNEL

bis(nonylphenyl)amine, CAS: 36878-20-3 ndustrial, dermal, Long-term - systemic effects: 5 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,25 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 2,5 mg/kg bw/day. Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 ndustrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day. ndustrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . ndustrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, inhalative, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, inhalative, Long-term - systemic effects: 0,24 mg/kg bw/day.
peneral population, oral, Long-term - systemic effects: 0,25 mg/kg bw/day. peneral population, dermal, Long-term - systemic effects: 2,5 mg/kg bw/day. Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day. industrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . industrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 industrial, inhalative, Long-term - systemic effects: 0,58 mg/kg bw/day. industrial, inhalative, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day.
peneral population, dermal, Long-term - systemic effects: 2,5 mg/kg bw/day. Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day. Industrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . Industrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . Industrial, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 Industrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. Industrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . Industrial, inhalative, Long-term - systemic effects: 0,24 mg/kg bw/day.
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 ndustrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day. ndustrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . ndustrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day.
ndustrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day. ndustrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . ndustrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day.
ndustrial, inhalative, Long-term - local effects: 5,6 mg/m ³ . ndustrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . jeneral population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
ndustrial, inhalative, Long-term - systemic effects: 2,7 mg/m ³ . jeneral population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. Industrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,24 mg/kg bw/day.
jeneral population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day. Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
ndustrial, dermal, Long-term - systemic effects: 0,58 mg/kg bw/day. ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
ndustrial, inhalative, Long-term - systemic effects: 8,31 mg/m ³ . general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
general population, oral, Long-term - systemic effects: 0,24 mg/kg bw/day. general population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
peneral population, dermal, Long-term - systemic effects: 0,29 mg/kg bw/day.
eneral population, inhalative, Long-term - systemic effects: 2,11 mg/m ³ .
C14-16-18 Alkyl phenol
ndustrial, dermal, Long-term - systemic effects: 0,3 mg/kg bw/day.
ndustrial, inhalative, Long-term - systemic effects: 1,17 mg/m ³ .

PNEC

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
seawater, 0,01 mg/l.
sewage treatment plants (STP), 1 mg/l.
sediment (freshwater), 132000 mg/kg.
freshwater, 0,1 mg/l.
sediment (seaater), 13200 mg/kg.
soil, 263000 mg/kg.
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
soil, 0,005 mg/kg.
sediment (seaater), 0,001 mg/kg dw.
sediment (freshwater), 0,012 mg/kg dw.
sewage treatment plants (STP), 100 mg/l.
seawater, 0,004 mg/l.
freshwater, 0,004 mg/l

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01

Page 5 / 11

oral (food), 10,67 mg/kg.	
C14-16-18 Alkyl phenol	
sediment (seaater), 426,62 mg/kg.	
sediment (freshwater), 0,1 mg/l.	
sediment (seaater), 0,01 mg/l.	
sediment (freshwater), 4266,16 mg/kg.	
soil, 852,58 mg/kg.	
oral (food), 3,3 mg/kg.	
sewage treatment plants (STP), 100 mg/l.	

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	If there is a risk of splashing: safety glasses
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Pa

Page 6 / 11

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	light brown
Odor	characteristic
Odour threshold	not applicable
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	> 200
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	0,842 (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	> 20,5 mm²/s (40° C) 14 mm²/s (100°C) (DIN 51562/T1)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.

9.2 Other information

Pour point: -36°C

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 7 / 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled .:
dermal, Based on the available information, the classification criteria are not fulfilled .:
oral, Based on the available information, the classification criteria are not fulfilled .:

Substance	
Bis(nonylphenyl)amine, CAS: 36878-20-3	
.D50, dermal, Rat: >2000 mg/kg (OECD 402).	
.D50, oral, Rat: >5000 mg/kg (OECD 401).	
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-	7
.D50, dermal, Rabbit: > 2000 mg/kg.	
.D50, oral, Rat: > 5000 mg/kg.	
.C50, inhalative, Rat: > 5,53 mg/l.	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4	
.D50, dermal, Rabbit: >3160 mg/kg bw/day.	
.D50, oral, Rat: 2600 mg/kg.	
.C50, inhalative, Rat: >2 mg/l.	
C14-16-18 Alkyl phenol	
.D50, dermal, Rat: >2000 mg/kg bw.	
.D50, oral, Rat (female): >2000 mg/kg bw.	

Serious eye damage/irritation	Toxicological data of complete product are not available. Irritant Calculation method
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Toxicological data of complete product are not available. May cause an allergic skin reaction. Calculation method
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	
	Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017

Version 01 Page 8 / 11

SECTION 12: Ecological information

12.1 Toxicity

Product
Based on the available information, the classification criteria are not fulfilled .:
Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Daphnia magna: >100 mg/l (OECD 202).
LC0, (96h), Brachidanio rerio: 58 mg/l (OECD 203).
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EL50, (24h), Daphnia magna: > 10000 mg/l.
NOELR, (14d), Oncorhynchus mykiss: >= 1000 mg/l.
LL50, (96h), Pimephales promelas: >100 mg/l.
NOEL, (72h), Pseudokirchneriella subcapitata: >= 100 mg/l.
NOEL, (21d), Daphnia magna: 10 mg/l.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4
EC50, (3h), Activated sludge: >10000 mg/l.
EC50, (72h), Selenastrum capricornutum: 2,1 mg/l.
EC50, (48h), Daphnia magna: 5,4 mg/l (OECD 202).
IC50, (21d), Daphnia magna: >0,8 mg/l.
LL50, (96h), Oncorhynchus mykiss: 4,5 mg/l.
C14-16-18 Alkyl phenol
LC50, (96h), Cyprinus carpio: >100 mg/l.
EC50, (24h), Daphnia magna: >100 mg/l.
EC50, (72h), Pseudokirchneriella subcapitata: >100 mg/l.
NOEC, (72h), Pseudokirchneriella subcapitata: 100 mg/l.
NOELR, (24h), Daphnia magna: >100 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017

SWAG[®]

Version 01 Page 9 / 11

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

	In according to RoHS! Coordinate disposal with the disposal contractor/authorities if necessary. Dispose of as hazardous waste.
Waste no. (recommended)	130205* mineral-based non-chlorinated engine, gear and lubricating oils
Contaminated packaging	
	Uncontaminated packaging may be taken for recycling. Packaging that cannot be cleaned should be disposed of as for product.
Waste no. (recommended)	150110*

SECTION 14: Transport information

14.1	UN number	
	Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable

Air transport in accordance with IATA not applicable

14.2	UN proper shipping name Transport by land according to ADR/RID	NO DANGEROUS GOODS
	Inland navigation (ADN)	NO DANGEROUS GOODS
	Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
	Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"
14.3	Transport hazard class(es) Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable

Marine transport in accordance with not applicable IMDG

Air transport in accordance with IATA not applicable

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017

Version 01 Page 10 / 11

14.4	Packing group Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.5	Environmental hazards	
	Transport by land according to ADR/RID	no
	Inland navigation (ADN)	no
	Marine transport in accordance with IMDG	no
	Air transport in accordance with IATA	no
14.6	Special precautions for user	
	Relevant information under SECTION 6	to 8.
14.7	Transport in bulk according to An	nex II of MARPOL and the IBC Code
	not applicable	
SEC	TION 15: Regulatory information	
15.1	Safety, health and environmental	regulations/legislation specific for the substance or mixture
	EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
	TRANSPORT-REGULATIONS	DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2018).
	NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
	- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
	- VOC (2010/75/CE)	0 %
15.2	Chemical safety assessment	
		not applicable
SEC	TION 16: Other information	

16.1 Hazard statements (SECTION 03)

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H413 May cause long lasting harmful effects to aquatic life.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

SWAG Autoteile GmbH 42117 Wuppertal

Date printed 07.03.2018, Revision 31.05.2017



Version 01 Page 11 / 11

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

- LC50 = Lethal concentration, 50%
- LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

none

TLV®/TWA = Threshold limit value - time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method) Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Modified position