



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

SAE 5W-40 C3

VAICO No.:

V60-0422, V60-0423, V60-0424, V60-0425, V60-0426, V60-0427, V60-0428

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

High performance engine oil for cars with petrol and diesel engines with low sulphur, ash and phosphorus content (low SAPS). Ensures high engine cleanliness and optimum wear protection.

3. PERFORMANCE DATA

3.1. Specifications:

ACEA C3 • API SN/CF

3.2. Fit to*:

Audi/VW 502 00 / 505 00 / 505 01

BMW Longlife-04

Fiat 9.55535-S2

Ford WSS-M2C917-A

GM dexos 2™

MB 226.5, 229.51

Porsche A40

Renault RN 0700 / 0710

TYPICAL VALUES	METHOD	UNIT	VAICO SAE 5W-40 C3
Density at 15°C	DIN 51 757	kg/m ³	850
Viscosity at 40°C	DIN 51 562	mm ² /s	80,1
Viscosity at 100°C	DIN 51 562	mm ² /s	13,6
Viscosity index (VI)	DIN ISO 2909	-	175
Viskosität bei -30°C	DIN 51 377	mPa.s	5250
Pour point	DIN ISO 3016	°C	-42
COC flash point	DIN ISO 2592	°C	232
Total base number	DIN ISO 3771	mg KOH/g	8,0

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.