



## 1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

---

### 1.1. Product identifier

Trade Name:

**VAICO ATF 8HP**

VAICO No.:

V60-0264, V60-0265, V60-0267, V60-0268

### 1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

## 2. PROPERTIES

---

- Excellent quality properties
- High load capacity, outstanding wear minimisation
- Exceptional friction coefficient consistency
- No foaming
- Very low evaporation loss
- Excellent gear shifting properties at low temperatures
- Adapted friction coefficient properties for sports-style gear shifting
- Outstanding oxidation and thermal stability
- No adverse effect on standard sealing materials

## 3. USE INSTRUCTIONS

---

- Specially designed for modern ZF 6-/8- and 9-speed automatic transmissions in high-powered vehicles
  - Not for use in DCT/DSG- (Double Clutch) or CVT- (Continuously-Automatic) transmissions suitable.
- Observe manufacturer instructions!

## 4. PERFORMANCE DATA

---

### 4.1. Fit to:\*

**Audi-VW** G 060 162 A1/-A2/-A6

**BMW** ATF 3/-3+, 83 22 2 305 397, 83 22 2 152 426 (L12108),  
83 22 2 289 720

**Chrysler** 68157995AA

**Fiat** 9.55550-AV5

**Jaguar** 02JDE26444

**Land Rover** LR 023288

**ZF** Lifeguard Fluid 8 (S671090312)



# PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO ATF 8HP
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,844
Viscosity at 40°C	DIN ISO 3104	mm <sup>2</sup> /s	26,9
Viscosity at 100°C	DIN ISO 3104	mm <sup>2</sup> /s	5,6
Viscosity index (VI)	DIN ISO 2909	-	157
COC flash point	DIN ISO 2592	°C	224
Pour point	DIN ISO 3016	°C	-45
Colour	-	-	green

\* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.