



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF III

VAICO No.:

V60-0078, V60-0079, V60-0080, V60-0081

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Extremely high viscosity index
- High load capacity, outstanding wear minimisation
- Low pour point
- No foaming
- High thermal stability
- Reliable friction coefficient characteristic
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Automatic motor vehicle transmissions and torque converters
- Hydrostatic transmissions
- Power steering systems
- Hydraulic systems

Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Fit to*:

Allison C-4

CAT TO-2

Ford Mercon

General Motors Dexron III-H

MAN 339 Typ Z1/-V1

MB 236.1, 236.5, 236.6, 236.7

Voith H55.6335.3X (G607)

Volvo 97341

ZF TE-ML 03D, 04D, 09, 11, 14A, 17C



PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO ATF III
Density at 15°C	DIN 51 757	g/cm ³	0.860
Viscosity at 40°C	DIN ISO 3104	mm ² /s	36
Viscosity at 100°C	DIN ISO 3104	mm ² /s	7.5
Viscosity index (VI)	DIN ISO 2909	-	176
COC flash point	DIN ISO 2592	°C	176
Pour point	DIN ISO 3016	°C	- 48
Colour	-	-	red

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances