



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF MB15

VAICO No.:

V60-0220, V60-0221, V60-0222, V60-0223

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Reduced viscosity for maximum fuel economy
- High load capacity, outstanding wear minimisation
- Exceptional friction coefficient consistency
- No foaming
- High thermal stability
- Smooth gear shifting even at low temperatures
- Unrivalled viscosity-temperature behaviour
- Excellent oxidation stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Specially designed for use in new Mercedes-Benz 7-speed automatic transmissions (NAG2FE+) from 21/06/2010
- ATF MB 15 is not suitable for use in older Mercedes-Benz automatic transmissions and is not backward compatible
- Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Fit to*:

MB 236.15, 001 989 77 03, 001 989 78 03, 001 989 78 03 10



PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO ATF MB15
Density at 15°C	DIN 51 757	g/cm ³	0.845
Viscosity at 40°C	DIN ISO 3104	mm ² /s	23
Viscosity at 100°C	DIN ISO 3104	mm ² /s	5
Viscosity index (VI)	DIN ISO 2909	-	160
COC flash point	DIN ISO 2592	°C	>190
Pour point	DIN ISO 3016	°C	-45
Colour	-	-	blue

* conforms to OEM specifications

The above values may vary within commercially accepted tolerances