



## 1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

---

### 1.1. Product identifier

Trade Name:

**VAICO VA-DOT 4**

VAICO No.:

V60-0242, V60-0074, V60-0075, V60-0111, V60-0445

### 1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

## 2. PROPERTIES

---

- 2.1. **HC-Synthetic fluid.**
- 2.2. **High dry and wet boiling point, reducing vapour bubble formation.**
- 2.3. **Excellent protection for all metal parts in the brake system against corrosion.**
- 2.4. **Good protection against wear and foaming.**
- 2.5. **Compatible with all seals and hoses installed in the brake system.**

## 3. USE INSTRUCTIONS

---

VAICO VA-DOT 4 is recommended for use in brake and clutch systems in vehicles that require a synthetic DOT 4 brake fluid. VAICO VA-DOT 4 can be mixed with all synthetic brake fluids of the same grade.

### 3.1. Special instructions:

- 3.1.1. Store brake fluid only in sealed original container.
- 3.1.2. Brake fluid can cause damage to vehicle paintwork.
- 3.1.3. Observe manufacturer instructions!

## 4. PERFORMANCE DATA

---

### Specifications:

FMVSS 116 DOT 3/ DOT 4

SAE J 1703 / J 1704

ISO 4925 class 6

### Suitable for:\*

**AUDI-VW** B 000 700 A3, B 000 700 B3, B 000 750 M3, BCN 000 700 Z3 | **FORD** 1 135 520

**GM** 90 187 662, 93 160 363 | **OPEL** 19 42 407, 19 42 426 (500ML)



# PRODUCT DATA



<b>TYPICAL VALUES</b>	<b>METHOD</b>	<b>UNIT</b>	<b>VAICO VA-DOT 4</b>
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	1.060
Viscosity at -40°C	DIN ISO 3104	mm <sup>2</sup> /s	<1350
Dry boiling point (min.)	DIN ISO 4925	°C	>260
Wet boiling point (min.)	DIN ISO 4925	°C	>155

\* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.